



PRODUCT SPECIFICATION

Quality		: CITY WALK
Construction		: Loop pile tip sheared
Dye method		: Solution dyed
Gauge		: Tufted 1/10"
No. of tufts	ISO 1763	: $\pm 118500/\text{m}^2$
Pile fibre		: 100% Nylon (PA 6)
Pile weight	ISO 8543	: $850 \text{ gr}/\text{m}^2 \pm 5\%$
Pile height	ISO 1766	: $3.5 \text{ mm} / 5.5 \text{ mm} \pm 5\%$
Primary backing		: Non-Woven
Tile backing		: Polyflex
Total thickness	ISO 1765	: $8.0 \text{ mm} \pm 5\%$
Total weight	ISO 8543	: $4000 \text{ gr}/\text{m}^2 \pm 7.5\%$
Tile size		: $50 \times 50 \text{ cm} (\pm 19.7'' \times 19.7'')$
Tiles per box		: 20



PERFORMANCE

Use classification	method en 1307	: 33
Castor chair test	EN 985 / EN ISO 4918	: intensive use
Abrasion	EN ISO 12951	: pass
Vettermann test	ISO 10361: 2015 / EN ISO 10833: 2019	: pass
Dimensional stability	EN 986	: pass
Luxury/Comfort	EN 1307	: LC3
Anti-slip property	EN 16165 method B	: R13



ELECTROSTATIC PROPERTIES

Static loading		: anti-static
----------------	--	---------------

FLAME PROPERTIES

Reaction to fire	EN ISO 11925-2 EN ISO 9239-1	: B _{fl} - s1
------------------	---------------------------------	------------------------



COLOUR FASTNESS PROPERTIES

Light	EN ISO 105 B02:2014	: 4
Rubbing, dry	EN ISO 105 X12:2016	: 4-5
Rubbing, wet	ISO 105 X12:2016	: 4-5
Water, change in colour	EN ISO 105-E01	: 4

GENERAL

Recommended maintenance:
Pile direction:

Best results are obtained when cleaned with a dry shampoo method.
Directional arrows are printed on the back of each tile.
Best results are obtained when laid quarter turn or brick.

Laying instructions:

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30 m² it is advisable to use double sided adhesive tape on every 8th row or a tackifier.

COLOURS

978
970
975
955

972
994
974
950

957
976
Polyflex backing
Felt backing